

# TECHNICAL DATA SHEET

[www.regalfloorpaint.co.uk](http://www.regalfloorpaint.co.uk)

## Antislip Quickdry Concrete Floor Paint

### Product Description & Recommended Use

- A single-pack, quick-drying floor-coating providing good durability and impact resistance.
- Moderate protection against solvents, salt and water-damage are a distinct advantage.
- In high-risk areas, which may be prone to pedestrian slippage, anti-slip properties meet most foot traffic requirements using a fine, aggregated-finish specially formulated to provide aesthetic and safe use.
- Suitable for medium-duty commercial and industrial areas.
- Easy to apply by roller and brush and easy to repaint on high wear areas.

Standard Colours	Slate Grey, Light Grey, Brunswick Green, Ford Tractor Blue, Cornflower Blue, Red Oxide, Post Office Red, Caterpillar Yellow, JCB Yellow, Chocolate Brown, Bright Orange, Black, White. Other RAL and British Standard colours can be made, dependent on the quantities required.
Dry Film Appearance	Sheen, textured
Spreading Rate	5-8m <sup>2</sup> per litre, dependent on film thickness
Touch Dry @20°C	3-4 hours
Recoating Time @20°C	Minimum 24 hours
Typical Wet-Film Thickness	105-170µm per coat
Typical Dry-Film Thickness	60-95µm per coat
Solids by Volume	58% (ASTM D2697) ±3%, dependent on colour
VOC Information	420g per litre (from formula to satisfy EU Solvent Emissions Directive)
Application Temperature	10-35°C
Application Method	Brush or roller
Substrates	Suitably cleaned and dry surfaces
Thinners	Thinning not recommended. For cleaning, use standard thinners.
Flash Point	>25°C
Pack Size	5 litre can; 20 litre can; 205 litre barrel
Shelf Life	12 months

### Key Benefits

- High Performance
- Quick Dry
- Anti-Slip Safety Product
- Formulated with High Quality Synthetic Resins

Complies with all current legislation at the time of writing.