

TECHNICAL DATA SHEET

www.regalfloorpaint.co.uk

Decorative Gloss

Product Description & Recommended Use

- A high-performance, easy-to-use gloss finish for internal and external applications.
- Made from long-oil alkyd and is lead and chrome-free (meets RoHS & CONEG requirements).
- Easy to apply by airless spray, conventional spray, roller or brush.
- Suitable for a wide-range of substrates including wooden doors and window frames, metal fencing and garage doors, and concrete walls.
- Easy to repaint.
- Not recommended for areas exposed to caustic-soda solutions or acids.
- Do not overbrush or opacity may be reduced.

Standard Colours	Slate Grey, Light Grey, Brunswick Green, Ford Tractor Blue, Cornflower Blue, Red Oxide, Post Office Red, Caterpillar Yellow, JCB Yellow, Chocolate Brown, Bright Orange, Black, White. Other RAL and British Standard colours can be made, dependent on the quantities required.
Dry Film Appearance	Gloss finish
Spreading Rate	7-15m ² per litre; 10m ² @50µm
Touch Dry @20°C	6-8 hours
Recoating Time @20°C	Minimum 16 hours (overnight recommended)
Typical Wet-Film Thickness	60-80µm per coat
Typical Dry-Film Thickness	30-40µm per coat
Solids by Volume	40% (ASTM D2697) ±3%, dependent on colour
VOC Information	470g per litre
Application Temperature	10-35°C
Application Method	Brush, roller or spray
Substrates	Suitably cleaned and dry surfaces.
Thinners	Thinning not recommended. For cleaning, use white spirit.
Flash Point	≥38°C
Pack Size	5 litre can; 20 litre can; 205 litre barrel
Shelf Life	12 months

Key Benefits

- High-Performance
- Ease of Application
- Formulated with Long-Oil Alkyd

Complies with all current legislation at the time of writing.