

## TECHNICAL DATA SHEET

[www.regalfloorpaint.co.uk](http://www.regalfloorpaint.co.uk)

### Regal Clear Finish

#### Product Description & Recommended Use

- Regal Clear Finish is a fast-drying, high gloss, clear, hard-wearing and protective finishing-coat.
- The hard, glossy finish will give your floor superb aesthetic appeal.
- Made with a tough, high quality, solvent-based acrylic co-polymer.
- Very good alkali and humidity resistance and excellent hardness.
- Can be applied over both the Regal Single-Pack and Regal Two-Pack flooring systems.
- Can be used to seal in decorative paint-flakes that are sprinkled onto the floor to give a granite effect.
- Can be mixed with metallic glitters to give a highly decorative finish to your floor. Ideal for shops, bars and other retail areas.

Standard Colours	None. This product is clear.
Dry Film Appearance	High Gloss
Spreading Rate	10m <sup>2</sup> per litre
Touch Dry @20°C	1-2 hours
Recoating Time @20°C	12 hours
Typical Wet-Film Thickness	45-75µm per coat
Typical Dry-Film Thickness	25-40µm per coat
Solids by Volume	48% (ASTM D2697) ±3%, dependent on colour
VOC Information	430g per litre
Application Temperature	10-35°C
Application Method	Brush or roller
Substrates	Suitably cleaned and dry surfaces
Thinners	Xylene
Flash Point	≥25°C
Pack Size	5 litre can; 20 litre can
Shelf Life	12 months

#### Key Benefits

- High Gloss
- Hard Wearing
- Superb Aesthetic Appeal
- Formulated with High-Quality Acrylic Copolymer

Complies with all current legislation at the time of writing.