

TECHNICAL DATA SHEET

www.regalfloorpaint.co.uk

Parlour Paint

Product Description & Recommended Use

- A high-performance, quick-drying paint which gives a tough, durable and smooth semi-gloss finish.
- Available in a limited range of popular colours to combine good cosmetic effect with an easy to clean and maintain finish.
- Made with high-quality synthetic resins and is lead and chrome-free.
- Suitable for general agricultural use where constant exposure to water and cleaning chemicals is likely.
- Specifically designed to protect against humidity and industrial pollution, safeguarding against chemical, acid or alkaline damage.
- Easy to apply by roller or brush.
- Easy to recoat with good cut-edge coverage.

Standard Colours	Slate Grey, Light Grey, Cornflower Blue, White. Other RAL and British Standard colours can be made, dependent on the quantities required.
Dry Film Appearance	Semi-gloss finish
Spreading Rate	4-6m ² per litre, depending on surface profile
Touch Dry @20°C	1-2 hours
Recoating Time @20°C	8-10 hours
Typical Wet-Film Thickness	150-200µm per coat
Typical Dry-Film Thickness	75-100µm per coat
Solids by Volume	52% (ASTM D2697) ±3%, dependent on colour
VOC Information	412g per litre
Application Temperature	6-35°C
Application Method	Brush or roller
Substrates	Suitably cleaned and dry surfaces.
Thinners	Thinning not recommended. For cleaning, use standard thinners.
Flash Point	≥25°C
Pack Size	5 litre can; 20 litre can; 205 litre barrel
Shelf Life	12 months

Key Benefits

- High-Performance
- Quick-Drying
- Easy to Clean
- Formulated with High-Quality Synthetic Resins

Complies with all current legislation at the time of writing.