

## PRODUCT DATA SHEET

[www.regalfloorpaint.co.uk](http://www.regalfloorpaint.co.uk)

### Quick Drying Gloss Enamel

#### Product Description & Recommended Use

- A tough, long-lasting, quick-drying gloss enamel with excellent durability.
- High impact resistance.
- Made from high-build alkyd and is lead and chrome-free.
- Easy to apply by airless spray, conventional spray or roller and brush.
- Suitable for general industrial use and structural steelwork.
- Compatible with most single-pack primers or can be applied as a single coat over existing enamel.
- Easy to recoat and with good cut-edge coverage.

Standard Colours	Slate Grey, Light Grey, Brunswick Green, Ford Tractor Blue, Cornflower Blue, Red Oxide, Post Office Red, Caterpillar Yellow, JCB Yellow, Chocolate Brown, Bright Orange, Black, White.
Dry Film Appearance	Gloss
Spreading Rate	5-10m <sup>2</sup> per litre
Touch Dry @20°C	3-6 hours.
Recoating Time @20°C	Minimum 16 hours
Typical Wet-Film Thickness	100-150µm per coat
Typical Dry-Film Thickness	50-75µm per coat
Solids by Volume	50% (ASTM D2697)
VOC Information	430g per litre
Application Temperature	10-35°C
Application Method	Airless spray, air-assisted spray (15-17 thou tip) brush or roller
Substrates	Suitably cleaned and dry surfaces.
Thinners	Thinning not recommended. For cleaning used standard thinners.
Flash Point	≥25°C
Pack Size	5 litre can; 20 litre can; 205 litre barrel
Shelf Life	12 months

#### Key Benefits

- Tough
- Quick-Dry
- Excellent Durability
- Formulated with High Quality Synthetic Resins

Complies with all current legislation at the time of writing.