

PRODUCT DATA SHEET

Quickdry Highbuild Floor Paint

Product Description & Recommended Use

- A single-pack, quick-drying, high-build floor-coating providing good durability and impact resistance.
- Moderate protection against solvents, salt, water and cleaning chemicals.
- Available as a semi-gloss finish in a range of colours specially formulated to provide good aesthetics and safe use.
- Suitable for medium-duty commercial and industrial areas.
- Easy to apply by roller and brush and easy to repaint on high-wear areas.

| | |
|----------------------------|---|
| Standard Colours | Slate Grey, Light Grey, Brunswick Green, Ford Tractor Blue, Cornflower Blue, Red Oxide, Post Office Red, Caterpillar Yellow, JCB Yellow, Chocolate Brown, Bright Orange, Black, White. Other RAL and British Standard colours can be made, dependent on the quantities required. |
| Dry Film Appearance | Semi-gloss (60-70%) |
| Spreading Rate | 5-8m ² per litre, dependent on film thickness (10m ² @ 50μm; 5m ² @ 100μ) |
| Touch Dry @20°C | 3-4 hours |
| Recoating Time @20°C | Minimum 24 hours |
| Typical Wet-Film Thickness | 105-195μm per coat |
| Typical Dry-Film Thickness | 85-110μm per coat |
| Solids by Volume | 60% (ASTM D2697) ±3%, dependent on colour |
| VOC Information | 420g per litre (from formula to satisfy EU Solvent Emissions Directive) |
| Application Temperature | 10-35°C |
| Application Method | Brush or roller |
| Substrates | Suitably cleaned and dry surfaces |
| Thinners | Thinning not recommended. For cleaning, use standard thinners. |
| Flash Point | >25°C |
| Pack Size | 5 litre can; 20 litre can; 205 litre barrel |
| Shelf Life | 12 months |

Key Benefits

- High Performance
- Quick Dry
- Formulated with High Quality Synthetic Resins

Complies with all current legislation at the time of writing.