

PRODUCT DATA SHEET

www.regalfloorpaint.co.uk

Agricultural Oxide

Product Description & Recommended Use

- A single-pack, good quality, easy-to-use, general-purpose coating, offering excellent weather resistance and durability.
- Made from high-quality alkyd resins.
- Tough, gloss-finish in a range of colours specially formulated for ease of application.
- Suitable for the agricultural industry; especially metal agricultural buildings, structural steel, and medium-duty industrial use.
- Can be applied to asbestos, wood and steel sheets.
- Easy to apply by spray or roller and brush and easy to repaint on high-wear areas.

Standard Colours	Slate Grey, Light Grey, Brunswick Green, Ford Tractor Blue, Cornflower Blue, Red Oxide, Post Office Red, Caterpillar Yellow, JCB Yellow, Chocolate Brown, Bright Orange, Black, White. Other RAL and British Standard colours can be made, dependent on the quantities required.
Dry Film Appearance	Gloss finish
Spreading Rate	5m ² per litre, dependent on film thickness.
Touch Dry @20°C	6 hours
Recoating Time @20°C	Minimum 18 hours
Typical Wet-Film Thickness	30-50µm per coat
Typical Dry-Film Thickness	20-30µm per coat
Solids by Volume	62%
VOC Information	295g per litre (from formula to satisfy EU Solvent Emissions Directive)
Application Temperature	6-35°C
Application Method	Spray, brush or roller
Substrates	Suitably cleaned and dry surfaces. Most interior or exterior substrate, especially metal agricultural buildings and structural steel. Can also be applied to asbestos, wood and steel sheets.
Thinners	Standard Thinner
Flash Point	≥32°C
Pack Size	5 litre can; 20 litre can; 205 litre barrel
Shelf Life	12 months

Key Benefits

- Tough
- Ease of Application
- Formulated with High Quality Alkyd Resins

Complies with all current legislation at the time of writing.