

## PRODUCT DATA SHEET

[www.regalfloorpaint.co.uk](http://www.regalfloorpaint.co.uk)

### Skip and Container Paint

#### Product Description & Recommended Use

- A durable, quick-air-drying, anti-corrosive one-coat paint which gives a tough semi-gloss finish.
- Made with high-quality alkyd resins and is lead and chrome-free.
- Suitable for direct-to-metal applications, such as brand new or refurbished skips and containers.
- Premium quality finish which offers resistance to some chemicals, oils and grease.
- Strong enough to provide protection against impacts and corrosion, ensuring to keep your equipment looking newer for longer.
- Formulated for application by airless spray. Also easy to apply by roller or brush.

Standard Colours	Slate Grey, Light Grey, Brunswick Green, Ford Tractor Blue, Cornflower Blue, Red Oxide, Post Office Red, Caterpillar Yellow, JCB Yellow, Chocolate Brown, Bright Orange, Black, White. Other RAL and British Standard colours can be made, dependent on the quantities required.
Dry Film Appearance	60-70% gloss finish
Spreading Rate	5-7 m <sup>2</sup> per litre
Touch Dry @20°C	15-30 minutes
Recoating Time @20°C	Minimum 12-14 hours
Typical Wet-Film Thickness	120-160µm per coat
Typical Dry-Film Thickness	65-90µm per coat
Solids by Volume	56% (ASTM D2697) ±3%, dependent on colour
VOC Information	430g per litre
Application Temperature	10-35°C
Application Method	Airless spray (15-17 thou tip), airless spray, brush or roller
Substrates	Suitably cleaned and dry surfaces
Thinners	Xylene
Flash Point	≥25°C
Pack Size	5 litre can; 20 litre can; 205 litre barrel
Shelf Life	12 months

#### Key Benefits

- High-Performance
- Quick-Drying
- Easy to Clean
- Formulated with High-Quality Synthetic Resins

Complies with all current legislation at the time of writing.